1. INTRODUCTION

This document identifies the component types that will be used in the External Harness for the Optical Monitor (OM3). The data is based on firm designs and is now practically complete. The components shown are accompanied by their flight specifications. Those used for the STM may be vacuum compatible devices to Military specifications.

2. REFERENCE DOCUMENTS

XMM-OM/MSSL/SP/0031	Product Assurance Plan
ESA PSS-01-60	Component Selection, Procurement and Control for ESA Space Systems
ESA/SCC 20100	Basic Specification Requirements for the Qualification of Standard Electronic Components for Space
XMM PX-RS-0017	Product Assurance Requirements for XMM Experiments

3. QUALITY LEVELS

Component selection and quality levels shall be as described in the PA Plan XMM-OM/MSSL/SP/0031.

4. TABLE DESCRIPTION

The format of the following table is as used in MSSL for identifying the types of components used, and the assemblies where they are used. It has been truncated just to show the component types and quantities.

CHANGE RECORD

ISSUE	DATE	PAGES CHANGED	COMMENTS
01	15 April 1997	All New	

CONTENTS

XMM Optical Monitor

MULLARD SPACE SCIENCE LABORATORY
UNIVERSITY COLLEGE LONDON **Author: A P Dibbens**

OM3 DECLARED COMPONENT LIST

Document Number: XMM-OM/MSSL/SP/0133.01 15 April 1997

Distribution:

XMM-OM Project Office	R Hunt	Orig.
ESA PX	H Eggel	
CSL	P Rochus	
	S. Roose	
UCSB	T Sasseen	
Royal Greenwich Observatory	R Bingham	
University College London	J Fordham	
Mullard Space Science Laboratory	N Bray	
	R Card	
	M Carter	
	R Chaudery	
	A Dibbens	
	H Huckle	
	H Kawakami	
	T Patrick	
	D Self	
	P Smith	
	P Thomas	
	M Whillock	
	K Mason	
	A Smith	

Author: Date:

OM Project Office Date:

Distributed: Date: